



FIRE & BURGLARY RESISTANT SAFE



FA55E

Features

- The Secuguard FA series safes are constructed from 6mm solid steel body and 12mm solid steel door to provide protection against both burglary and fire.
- Designed to give ½ hour fire resistance (when properly installed).
- Expanding fire seal around door frame.
- 25mm diameter solid steel active locking bolts.
- High Quality Securam UL certified electronic digital safe lock.
- Drill resistant hardened steel plate to protect lock area
- Secondary re-locking device (FA35E & FA55E only).
- Programmable code.
- Errant access lockout feature.
- Battery compartment is located within the keypad housing.
- Full internal carpet lining to walls and shelves.
- Two bolt holes in base for fixing with anchor bolts.
- Durable powder coated finish in cream colour.



FA35E



FA22E

Specifications

Model	Lock type	External dimensions (mm)			Internal dimensions (mm)			Removable shelves	Weight (kgs)
		Height	Width	Depth	Height	Width	Depth		
FA22E	SecuRam digital lock	222	352	300	180	310	204	1 x fixed	34
FA35E	SecuRam digital lock	352	452	350	310	410	254	1 x fully adjustable	61
FA55E	SecuRam digital lock	552	452	350	510	410	254	1 x fully adjustable	85

Depth measurement does not include the handle, keypad or hinges (please allow 50mm). Warranty: 12 month warranty excluding freight and travelling. The safe pictures shown on this brochure are for illustrative purpose only. Weights and dimensions are approximate. We reserve the right to alter specifications without notice or obligation.