



SHS4E



SHS4E



SHS2E



SHS2E / SHS2K



SHS2K



SHS1K



SHS1K

Key Features

- Solid steel construction with 6mm steel plate body reinforced with steel bar all around front edges. Solid 12mm steel plate door with internal hinges.
- Drill resistant hardened steel plate to protect lock area.
- 32mm solid steel active locking bolts (excluding SHS1K).
- Chrome plated tri-spoke handle (excluding SHS1K).
- Carpet to floor and shelves.
- 4 x 15mm anchor bolt holes in base and back.
- Durable powder coated hammertone finish in charcoal.
- **Safe with keylock:** Quality Australian made pick resistant Ross lever key lock.
- **Safe with mechanical combination lock:**
 - Quality UL listed mechanical combination lock.
 - Secondary spring-loaded re-locking device.
- **Safe with electronic digital lock:**
 - Quality UL listed SecuRam electronic digital safe lock.
 - Secondary spring-loaded re-locking device.
 - Programmable manager code and user code.
 - Universal lock footprint for easy lock conversion. Audit trail, time delay, dual control mode, Bluetooth, multi-user, biometric, access control and emergency key override available at an additional cost.
 - Errant access lockout feature.
 - Battery compartment is located within the keypad housing.

Specifications

Model	Lock type	External dimensions (mm)			Internal dimensions (mm)			Shelves (removable)	Weight (kgs)
		Height	Width	Depth	Height	Width	Depth		
SHS1K	Ross key lock	200	260	200	188	248	129 / 162	NIL	18
SHS2K	Ross key lock	250	360	260	238	348	165	1	34
SHS2C	Mechanical combination lock	250	360	260	238	348	165	1	34
SHS2E	SecuRam digital lock	250	360	260	238	348	165	1	34
SHS3K	Ross key lock	300	400	310	238	388	215	1	44
SHS3C	Mechanical combination lock	300	400	310	288	388	215	1	44
SHS3E	SecuRam digital lock	300	400	310	288	388	215	1	44
SHS4K	Ross key lock	500	400	360	488	378	265	2 fully adjustable	68
SHS4C	Mechanical combination lock	500	400	360	488	378	265	2 fully adjustable	68
SHS4E	SecuRam digital lock	500	400	360	488	378	265	2 fully adjustable	68

Depth measurement does not include the handle, keypad or hinges (please allow 50mm). Warranty: 12 month warranty excluding freight and travelling. The safe pictures shown on this brochure are for illustrative purpose only. Weights and dimensions are approximate. We reserve the right to alter specifications without notice or obligation.