



Features

- Solid steel construction with 6mm steel plate body and laser cut 12mm steel plate door and face.
- Concealed internal hinges with a reinforced internal full length dead bar .
- Drill resistant hardened steel plate to protect lock area.
- 32mm solid steel bolt work.
- Chrome plated tri-spoke handle.
- 160mm x 15mm posting slot fitted with jagged teeth baffle device.
- 4 x 15mm bolt holes in base and 2 x 15mm bolt holes in back.
- Durable powder coated hammertone finish in charcoal.
- **Safe with keylock**
 - ♦ Quality Australian made pick resistant Ross lever key lock.
- **Safe with mechanical combination lock**
 - ♦ Quality UL listed mechanical combination lock.
 - ♦ Secondary spring-loaded re-locking device.
- **Safe with electronic digital lock**
 - ♦ Quality UL listed SecuRAM electronic digital safe lock.
 - ♦ Programmable manager code and user code.
 - ♦ Errant access lockout feature.
 - ♦ This digital keypad features a rugged construction with heavy-duty stainless steel housing.
 - ♦ Battery compartment is located within the keypad housing.
 - ♦ Secondary spring-loaded re-locking device.
 - ♦ Universal lock footprint for easy lock conversion. Audit trial, time delay, dual control, bluetooth, multi-user, timelock and emergency key override available at an additional cost.



Specifications

Model	Lock type	External dimensions (mm)			Weight (kgs)	RRP (incGST)
		Height	Width	Depth		
CS252K	Ross key lock	300	350	250	34	
CS252C	Mechanical combination lock	300	350	250	34	
CS252E	SecuRAM digital lock	300	350	250	34	

Depth measurement does not include the handle, keypad or hinges (please allow 50mm). Warranty: 12 month warranty excluding freight and travelling.
The safe pictures shown on this brochure are for illustrative purpose only. Weights and dimensions are approximate. We reserve the right to alter specifications without notice or obligation.